



SUPER PLAST (CYS EN 998-1:2010)



ADVANCE BUILDING INDUSTRIES
Borg El Arab –Industrial Zone – Phase 4
P.O. BOX 158
Alexandria – Egypt

12

CYS EN 998-1:2010

General Purpose rendering / plastering mortar (GP) for external and internal use CSII

Reaction to fire: Class A1

Adhesion: 0,25 N/mm² – FP:B

Water absorption: W0

Water vapour diffusion coeff.: μ 25 (tab. value)

Thermal conductivity ($\lambda_{10, dry}$): P = 50% $\lambda = 0,47$ W/mK (tab. values)

Durability: (against freeze/thaw): excellent (evaluation based on provisions valid indented place of use of the mortar)

Dangerous Substances: See technical data and related marking

CYPRUS: Head Office: Michali Zeipekki 23, 4525 Moni - Limassol, Cyprus. Tel: +357 25632642, Fax: +357 25632091, E-mail:

zeiplast@zeiplast.com

EGYPT: A.B.I. Borg El-Arab, Alexandria, Egypt, Industrial Zone, Phase 4. Tel: +203 4595967/8/9, Fax: +203 4595971, E-mail:

adbuilding_eg@yahoo.com

SAUDI ARABIA: P.M.I. Al Khumrah Industrial Area, Jeddah, Saudi Arabia. Tel/Fax: +966 266 29901/2/3, E-mail:

pmisajed@yahoo.com

UAE: Zeiplast Emirates. Delma St., Abu Dhabi, U.A.E P.O.Box 42591. Tel: +971 24 456789, Fax: +971 24 456788 E-mail:

zeiplast@eim.ae