



## UP-LIGHT ( CYS EN 998-1:2010)



**ADVANCE BUILDING INDUSTRIES**  
Borg El Arab –Industrial Zone – Phase 4  
P.O. BOX 158  
Alexandria – Egypt

**12**

### **CYS EN 998-1:2010**

#### **Lightweight rendering / plastering mortar (LW) for external and internal use CSII**

Reaction to fire: Class A1

Adhesion: 0,3 N/mm<sup>2</sup> -FP:B

Water absorption: W0

Water vapour diffusion coeff.:  $\mu$  25 (tab. value)

Thermal conductivity ( $\lambda_{10, dry}$ ): 0.37 W/mK

Durability: (against freeze/thaw): excellent (evaluation based on provisions valid indented place of use of the mortar)

Dangerous Substances: See technical data and related marking

CYPRUS: Head Office: Michali Zeipekki 23, 4525 Moni - Limassol, Cyprus. Tel: +357 25632642, Fax: +357 25632091, E-mail:

[zeiplast@zeiplast.com](mailto:zeiplast@zeiplast.com)

EGYPT: A.B.I. Borg El-Arab, Alexandria, Egypt, Industrial Zone, Phase 4. Tel: +203 4595967/8/9, Fax: +203 4595971, E-mail:

[adbuilding\\_eg@yahoo.com](mailto:adbuilding_eg@yahoo.com)

SAUDI ARABIA: P.M.I. Al Khumrah Industrial Area, Jeddah, Saudi Arabia. Tel/Fax: +966 266 29901/2/3, E-mail:

[pmisajed@yahoo.com](mailto:pmisajed@yahoo.com)

UAE: Zeiplast Emirates. Delma St., Abu Dhabi, U.A.E P.O.Box 42591. Tel: +971 24 456789, Fax: +971 24 456788 E-mail:

[zeiplast@eim.ae](mailto:zeiplast@eim.ae)